

KPZ 200

Braided hose, two-layer, EN857 2SC, twin hose

HANSA FLEX

Last updated: 16/06/2026

Properties

Inner tube	oil resistant, synthetic rubber
Reinforcement	two high-tensile steel wire braids
Cover	oil resistant and weatherproof synthetic rubber
Application	medium pressure circuits with restricted installation spaces
Colour	black
Elongation	+ 2 % to - 4 %
Media	mineral oil poly-glycol based oil water (0 °C to +70 °C) water-oil-emulsions
Special features	small bend radius
Standard	EN 857 2SC
Temp. max.	100 °C
Temp. min.	-40 °C
Customs tariff number	40092100



The product image may differ

Items

Identification	D N*	Inch	Si ze	Inside Ø (mm)	Outside Ø (mm)	Working pressure (bar)	Ø Reinforcement (mm)	Test pressure (bar)	Burst pressure (bar)	Bend radius min. (mm)
KPZ 206	6	1/4"	4	6.4	13.5	400	11.1	800	1,850	45
KPZ 208	8	5/16"	5	8	15.3	350	12.9	700	1,700	55
KPZ 210	10	3/8"	6	9.5	17.4	330	15	660	1,550	65
KPZ 213	12	1/2"	8	12.7	21	275	18.6	550	1,270	80

DN = nominal diameter, nominal width

Suitable Frames

PHD 100	Swage ferrule for braided hose, skive ferrule, steel
---------	--