

KP 200 NO

Braided hose, two-layer, EN857 2SC, higher ozone resistance

HANSA FLEX

Last updated: 17/06/2026

Properties

Inner tube	oil resistant, synthetic rubber
Reinforcement	two high-tensile steel wire braids
Cover	synthetic rubber with high ozone, abrasion, and weather resistance
Application	medium pressure circuits with restricted installation spaces and extreme environmental conditions
Colour	black
Elongation	+ 2 % to - 4 %
Standard	EN 857 2SC
Temp. max.	100 °C
Temp. min.	-40 °C
Customs tariff number	40092100



The product image may differ

Note

The change in length of the hose is determined at max. working pressure during testing according to EN ISO 1402

Items

Identification	DN*	Inch	Size	Inside Ø (mm)	Outside Ø (mm)	Working pressure (bar)	Test pressure (bar)	Burst pressure (bar)	Bend radius min. (mm)
KP 206 NO	6	1/4"	4	6.4	14	400	800	1,600	75
KP 208 NO	8	5/16"	5	7.9	15.6	350	700	1,400	85
KP 210 NO	10	3/8"	6	9.5	17.8	330	660	1,320	90
KP 213 NO	12	1/2"	8	12.7	21.3	275	550	1,100	130

DN = nominal diameter, nominal width

Suitable Frames

PHD 100	Swage ferrule for braided hose, skive ferrule, steel
---------	--