


### Properties

Inner tube	polyamide (PA)
Reinforcement	four spirals of high-tensile steel wire
Cover	polyurethane (PUR)
Application	extreme pressure applications high pressure tools emergency rescue systems jaws of life
Media	mineral oil water (0 °C to +70 °C) Water-oil emulsions (up to +70 °C).
Special features	twin hose Abrasion resistant cover. Highly flexible and compact.
Temp. max.	100 °C
Temp. min.	-40 °C
Working pressure	720 bar
Burst pressure	2,880 bar
Customs tariff number	39173100



The product image may differ

### Items

Identification	DN*	Inch	Size	Inside Ø (mm)	Outside Ø (mm)	Colour	Test pressure (bar)	Bend radius min. (mm)
NYZ 7206 B	6	(6 mm) 1/4"	4	6.4	12.5	blue	1,440	70
NYZ 7206 BGE	6	(6 mm) 1/4"	4	6.4	12.5	blue + yellow	1,440	70
NYZ 7206 BR	6	(6 mm) 1/4"	4	6.4	12.5	blue + red	1,440	70
NYZ 7206 GE	6	(6 mm) 1/4"	4	6.4	12.5	yellow	1,440	70
NYZ 7206 R	6	(6 mm) 1/4"	4	6.4	12.5	red	1,440	70

DN = nominal diameter, nominal width

### Accessories

PKF	Kink protection, spring
-----	-------------------------

### Fittings

PNY 7200 AB	Swage nipple for thermoplastic hose NY7200, DKR, union nut, straight, steel
PNY 7200 AOS	Swage nipple for NY7200, DKOS, heavy series, union nut, straight, steel
PNY 7200 HN	Swage nipple for NY7200, AGN, external thread, straight, steel

### Suitable Frames

PHY 7200	Swage ferrule for NY7200, steel
----------	---------------------------------