


Properties

Inner tube	polyamide (PA)
Reinforcement	four spirals of high-tensile steel wire
Cover	polyurethane (PUR)
Application	extreme pressure applications high pressure tools emergency rescue systems jaws of life
Media	mineral oil water (0 °C to +70 °C) Water-oil emulsions (up to +70 °C).
Special features	Abrasion resistant cover. Highly flexible and compact.
Temp. max.	100 °C
Temp. min.	-40 °C
Customs tariff number	39173100



The product image may differ

Items

Identification	D N*	Inch	Si ze	Inside Ø (mm)	Outside Ø (mm)	Color	Working pressure (bar)	Test pressure (bar)	Burst pressure (bar)	Bend radius min. (mm)
NY 7206	6	1/4"	4	6.4	12.5	black	720	1,440	2,880	70
NY 7206 B	6	(6 mm) 1/4"	4	6.4	12.5	blue	720	1,440	2,880	70
NY 7206 GE	6	(6 mm) 1/4"	4	6.4	12.5	yellow	720	1,440	2,880	70
NY 7206 R	6	(6 mm) 1/4"	4	6.4	12.5	red	720	1,440	2,880	70

DN = nominal diameter, nominal width

Accessories

PKF	Kink protection, spring
-----	-------------------------

Fittings

PNY 7200 AB	Swage nipple for thermoplastic hose NY7200, DKR, union nut, straight, steel
PNY 7200 AOS	Swage nipple for NY7200, DKOS, heavy series, union nut, straight, steel
PNY 7200 HN	Swage nipple for NY7200, AGN, external thread, straight, steel

Suitable Frames

PHY 7200	Swage ferrule for NY7200, steel
----------	---------------------------------