

TE 200 B


Textile hose, EN854 2TE

HANSA FLEX

Last updated: 12/06/2026

Properties

Inner tube	oil resistant, synthetic rubber
Reinforcement	one or two textile braids
Cover	oil resistant and weatherproof synthetic rubber
Application	low pressure hose for general applications
Colour	black
Media	mineral oil glycol water (0 °C to +70 °C) water-oil-emulsions
Standard	EN 854 2TE
Temp. max.	100 °C
Temp. min.	-40 °C
Customs tariff number	40093100



The product image may differ

Items

Identification	D N*	Inch	Si ze	Inside Ø ma x. (mm)	Outside Ø min. (mm)	Outside Ø ma x. (mm)	Working pressure (bar)	Test pressu re (bar)	Burst pressure (bar)	Bend radius min. (mm)	Inside Ø (mm)
TE 204 B	5	3/16"	3	5.2	11.6	12.2	80	160	320	35	
TE 206 B	6	1/4"	4	6.9	13	13.6	75	150	300	40	
TE 208 B	8	5/16"	5	8.4	14.6	15.2	68	136	272	50	
TE 210 B	10	3/8"	6	10	16.2	16.8	63	126	252	60	
TE 213 B	12	1/2"	8	13.3	19.2	19.8	58	116	232	70	
TE 216 B	16	5/8"	10	16.5	23.6	24.4	50	100	200	90	
TE 220 B	19	3/4"	12	19.8	26.6	27.4	45	90	180	110	
TE 225 B	25	1"	16	26.2	33.3	34.1	40	80	160	150	
TE 232 B	31	1.1/4"	20	32.8	42.3		35	70	140	140	31.8

DN = nominal diameter, nominal width

Suitable Frames

PHT	Swage ferrule for TE200, TE300, steel
PHT 200	Swage ferrule for TE200, steel