

TE 300 B


Low pressure hose with textile insert

HANSA FLEX

Last updated: 17/06/2026

Properties

Inner tube	synthetic rubber NBR
Reinforcement	two textile braids
Cover	flame retardant, oil resistant, weatherproof synthetic rubber
Application	low pressure hose for general applications
Colour	black
Media	mineral oil base light heating oil lubricating oil water air (up to +70 °C) water-glycol emulsions
Standard	EN 854 3TE
Temp. max.	100 °C
Temp. min.	-40 °C
Customs tariff number	40093100



The product image may differ

Items

Identification	D N*	Inch	Si ze	Inside Ø (mm)	Outside Ø (mm)	Color	Test pressure (bar)	Working pressure (bar)	Burst pressure (bar)	Bend radius min. (mm)
TE 306 B	6	1/4"	4	6.4	14.4	black	290	145	580	45
TE 308 B	8	5/16"	5	7.9	16.9	black	260	130	520	55
TE 310 B	10	3/8"	6	9.5	18.5	black	220	110	440	70
TE 313 B	12	1/2"	8	12.7	21.7	black	186	93	372	85
TE 316 B	16	5/8"	10	15.8	25.9	black	160	80	320	105
TE 320 B	19	3/4"	12	19	29	black	140	70	280	130
TE 325 B	25	1"	16	25.4	35.9	black	110	55	220	150
TE 332 B	31	1.1/4"	20	31.8	42.3	black	90	45	180	190

DN = nominal diameter, nominal width